



## 4-Post Boat Lifts

- All Aluminum and Stainless Steel Construction
- Available in Multiple Drive Configurations including:
  - Direct Drive (no belts or chains)
  - Sealed Gearbox Belt Drive
  - Ultra Fast Direct Drive (G3)
  - Marine Duty Stainless Steel Motors
- "Quick Adjust" Stainless Steel Cables
- Heavy Duty, easily adjustable Guide Poles
- Extruded Aluminum Bearing Blocks
- Welded Construction (not bolted)
- Aluminum Pulleys with Stainless Steel Axle Bolts & Grease Fittings
- Optional SEArmor Corrosion Resistant Package
- 10 Year Limited Warranty

### Additional Options:

- Wireless Remote Control
- Limit Switch with Auto Stop
- Aluminum Bunks (Up to 20,000 lbs.)

\*\*\*See our "Complete list of Other Accessories"



## Specifications

Size	Top Carrier Dimensions	Lifter Beam Dimensions	Horse Power	Volt and Amperage	Cable Size and Length	Vertical Travel	Bunks	Minimum Pile Size
4,500 lb.	5" x 12' 6" Channel	6" x 11'0" I-Beam	(2) 3/4 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 20' Stainless Steel	12'+	3" x 8" x 12' Carpeted Bunks	(4) 8" Pilings
7,000 lb.	5" x 12' 6" Channel	6" x 12'0" I-Beam	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 20' Stainless Steel	12'+	3" x 8" x 12' Carpeted Bunks	(4) 8" Pilings
10,000 lb.	6" x 12'6" Channel	8" x 12'6" I-Beam	(2) 3/4 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 32' Stainless Steel	12'	3" x 8" x 12' Carpeted Bunks	(4) 8" Pilings
13,000 lb.	7" x 12'6" Channel	8" x 12'6" I-Beam	(2) 1 HP Stainless Steel*	120V/30A 240V/20A	5/16" x 32' Stainless Steel	12'	3" x 10" x 12' Carpeted Bunks	(4) 8" Pilings
16,000 lb.	7" x 12'6" Channel	10" x 14' I-Beam	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 32' Stainless Steel	12'	3" x 10" x 14' Carpeted Bunks	(4) 10" Pilings
20,000 lb.	8" x 12'6" Channel	10" x 14' I-Beam	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 48' Stainless Steel	12'	3" x 10" x 14' Carpeted Bunks	(4) 10" Pilings
24,000 lb.	8" x 15'0" Channel	12' x 15' I-Beam	(2) 1 HP Stainless Steel*	240V/20A	5/16" x 48' Stainless Steel	12'	3" x 12" x 18' Carpeted Bunks	(4) 10" Pilings
30,000 lb. (w/remote)	8" x 15'0" Channel	12" x 16' I-Beam	(4) 1 HP Stainless Steel*	240V/30A	3/8" x 50' Stainless Steel	12'	3" x 12" x 20' Carpeted Bunks	(4) 10" Pilings

\*Stainless Steel Motors are Standard on all Direct Drive and H2 High Speed Direct Drive Lifts Only